

C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 1 / 11

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: C1.12
Product name C1.12

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Protective neutral detergent washes and waxes

1.3. Details of the supplier of the safety data sheet

Name ITALIAN XS SRL - XSTONE

Full address Via Del Mulino 25 - Zona Artigianale

District and Country 64039 Penna Sant'Andrea (TE)

Italia

Tel. +39 0861.650578 Fax +39 0861.1755862

e-mail address of the competent person

responsible for the Safety Data Sheet office@italianxs.com

1.4. Emergency telephone number

For urgent inquiries refer to Centro Antiveleni 24/24 h

Policlinico A. Gemelli (Roma)

Tel. +39 06.3054343

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P280 Wear eye protection / face protection.

P337+P313 If eye irritation persists: Get medical advice / attention.

2.3. Other hazards



C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 2 / 11

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

DIPROPYLENE GLYCOL MONOMETHYL ETHER

CAS $34590-94-8 \quad 2 \le x < 2,5$ Eye Irrit. 2 H319

EC 252-104-2

INDEX

NOPOL ETHOXYLATED PROPOXYLATED

CAS 174955-61-4 1,5 ≤ x < 2 Acute Tox. 4 H302, Eye Dam. 1 H318

EC

INDEX

1-METHOXY-2-PROPANOL

CAS 107-98-2 $1.5 \le x < 2$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-539-1 INDEX 603-064-00-3

Reg. no. 01-2119457435-35-XXXX

2-BUTOXYETHANOL

CAS 111-76-2 1 ≤ x < 1,5 Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319,

Skin Irrit. 2 H315

EC 203-905-0 INDEX 603-014-00-0

Reg. no. 01-2119475108-36-XXXX

ALKYL DIMETHYL BETAINE

CAS 66455-29-6 0,89 ≤ x < 1 Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1,

Aquatic Chronic 3 H412

EC 266-368-1

INDEX

1,3 PROPANEDIAMINE

CAS 139734-65-9 0,3 ≤ x < 0,35 STOT RE 1 H372, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1,

Aquatic Chronic 3 H412

EC INDEX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

. SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.



C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 3 / 11

SECTION 5. Firefighting measures .../>>

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU Deutschland TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und

Kurzzeitwerte

ESP España LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019

(INSST)

FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

GBR United Kingdom EH40/2005 Workplace exposure limits (Third edition, published 2018)

ITA Italia DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017



C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 4 / 11

SECTION 8. Exposure controls/personal protection/>>

EU OEL EU

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC;

Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2019

DIPROPYLENE GLYCOL MONOMETHYL ETHER									
Threshold Limit Value									
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	310	50	310	50				
MAK	DEU	310	50	310	50				
VLA	ESP	308	50			SKIN			
VLEP	FRA	308	50			SKIN			
WEL	GBR	308	50			SKIN			
VLEP	ITA	308	50			SKIN			
OEL	EU	308	50			SKIN			
TLV-ACGIH		606	100	909	150	SKIN			

1-METHOXY-2-PROPANOL									
Threshold Limit	Value								
Type Country		TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	370	100	740	200				
MAK	DEU	370	100	740	200				
VLA	ESP	375	100	568	150	SKIN			
VLEP	FRA	188	50	375	10	SKIN			
WEL	GBR	375	100	560	150	SKIN			
VLEP	ITA	375	100	568	150	SKIN			
TLV-ACGIH		184	50	368	100				

				2-BUTO	XYETHANO	L			
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15	min	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
VLA	ESP	98	20	245	50	SKIN			
VLEP	FRA	9,8	2	147,6	30	SKIN			
WEL	GBR		25		50	SKIN			
TLV-ACGIH		97	20						

Legend

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS



ITALIAN XS SRL - XSTONE

C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 5 / 11

Information

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties		Value
Appearance		liquid
Colour		colourless
Odour		aromatic
Odour threshold		Not available
рН		Not available
Melting point / freezing point		Not available
Initial boiling point		Not available
Boiling range		Not available
Flash point	>	60 °C
Evaporation rate		Not available
Flammability (solid, gas)		Not available
Lower inflammability limit		Not available
Upper inflammability limit		Not available
Lower explosive limit		Not available
Upper explosive limit		Not available
Vapour pressure		Not available
Vapour density		Not available
Relative density		Not available
Solubility		Not available
Partition coefficient: n-octanol/water		Not available
Auto-ignition temperature		Not available
Decomposition temperature		Not available
Viscosity		Not available
Explosive properties		Not available
Oxidising properties		Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

1-METHOXY-2-PROPANOL

Dissolves various plastic materials. Stable in normal conditions of use and storage.

Absorbs and disolves in water and in organic solvents. With air it may slowly form explosive peroxides.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

1-METHOXY-2-PROPANOL

May react dangerously with: strong oxidising agents, strong acids.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.



ITALIAN XS SRL - XSTONE

C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 6 / 11

SECTION 10. Stability and reactivity .../>>

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

1-METHOXY-2-PROPANOL

Avoid exposure to: air.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

1-METHOXY-2-PROPANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

1-METHOXY-2-PROPANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

1-METHOXY-2-PROPANOL

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product. Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: > 20 mg/l
LD50 (Oral) of the mixture: >2000 mg/kg
LD50 (Dermal) of the mixture: >2000 mg/kg

1-METHOXY-2-PROPANOL

 LD50 (Oral)
 5300 mg/kg Rat

 LD50 (Dermal)
 13000 mg/kg Rabbit

 LC50 (Inhalation)
 54,6 mg/l/4h Rat

1,3 PROPANEDIAMINE

LD50 (Oral) > 300 mg/kg

2-BUTOXYETHANOL

LD50 (Oral) > 300 mg/kg Ratto LD50 (Dermal) > 1000 mg/kg Rabbit



C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 7 / 11

SECTION 11. Toxicological information .../>>

LC50 (Inhalation)

> 10 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

1,3 PROPANEDIAMINE

 LC50 - for Fish
 43 mg/l/96h

 EC50 - for Crustacea
 11 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 5 mg/l/72h

2-BUTOXYETHANOL

 LC50 - for Fish
 > 100 mg/l/96h

 EC50 - for Crustacea
 > 100 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

ALKYL DIMETHYL BETAINE

LC50 - for Fish 43 mg/l/96h Pesci EC50 - for Crustacea 11 mg/l/48h Crostacei

EC50 - for Algae / Aquatic Plants 5 mg/l/72h

NOPOL ETHOXYLATED PROPOXYLATED

EC50 - for Crustacea > 100 mg/l/48h

12.2. Persistence and degradability



C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 8 / 11

SECTION 12. Ecological information .../>>

1-METHOXY-2-PROPANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

ALKYL DIMETHYL BETAINE

Entirely degradable

NOPOL ETHOXYLATED PROPOXYLATED

Rapidly degradable

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

1-METHOXY-2-PROPANOL

Partition coefficient: n-octanol/water < 1

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Partition coefficient: n-octanol/water 0,0043

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable



ITALIAN XS SRL - XSTONE

C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 9 / 11

SECTION 14. Transport information .../>>

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

Eye Dam. 1 Serious eye damage, category 1
Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H226Flammable liquid and vapour.H302Harmful if swallowed.H312Harmful in contact with skin.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage.



ITALIAN XS SRL - XSTONE

C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 10 / 11

SECTION 16. Other information .../>>

H319 Causes serious eye irritation.H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

XSTONE

ITALIAN XS SRL - XSTONE

C1.12 - C1.12

Revision nr.1 Dated 15/12/2022 First compilation Printed on 15/12/2022 Page n. 11 / 11

This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.